

Coastal Guardian

Multicat 2209

JUN 20 2025



MAIN SPECIFICATIONS

General

| | |
|-------------------|--|
| Type of vessel: | Special Service / Multi purpose ship |
| Classification: | 1 ⚓ Hull • Mach • AUT-UMS Coastal area |
| IMO: | 9447093 |
| Callsign : | PHKF |
| MMSI: | 244564000 |
| Flag: | Dutch |
| Tonnage (UMS/GT): | 135 |

Dimensions

| | |
|-------------------------|--|
| Length O.A.: | 21.60 m |
| Beam O.A.: | 9.04 m |
| Draught aft (range): | 1.52 m – 2.05 m Nozzle/rudder ext. below keel + 0.32 m |
| Max deadweight tonnage: | 130 t |
| Clear deck area: | FWD deck approx. 67 m ² AFT deck approx. 40 m ² |
| Deck loading: | 6 t/m ² |

Tank Capacities

| | |
|-------------------|---------------------|
| Fuel oil: | 56 m ³ |
| Fresh water: | 28 m ³ |
| Black/grey water: | 5 m ³ |
| Ballast water: | 32 m ³ |
| Dirty oil: | 1.60 m ³ |

Accommodation

| | |
|---------|------------------------|
| POB: | 6 Fully airconditioned |
| Cabins: | 3 double |

Performances

| | |
|---------------------|------|
| Bollard pull ahead: | 14 t |
|---------------------|------|

Navigation & Communication

| | |
|--------|------------|
| GMDSS: | A1, A2, A3 |
|--------|------------|

JIFMAR GROUP

→ Contact: sales@jifmar.net



This document is for guidance and information only. Information provided is given under good faith and is non-contractual. This document may be updated without advanced notice. It may not be published, redistributed or reproduced without the prior written consent of ©Jifmar Group.



DETAILED SPECIFICATIONS

Propulsion System

| | |
|---------------|---|
| Main engines: | 2 x Caterpillar C-18 ACERT 447 kW Twin fixed propellers in nozzles |
| Power output: | 894 kW |

Auxiliary Systems

| | |
|-----------------|---|
| Generator sets: | John Deere 6081 189 kVA – 400 V / 50 Hz John Deere 4045 81 kVA – 400 V / 50 HZ |
|-----------------|---|

Deck Lay-out

| | |
|-----------------------|--|
| Crane FWD: | Heila HLRM-3S 140 tm Fixed hook SWL 10 t - 12 m |
| Anchor handling drum: | 50 t - 7 m/min. 25 t - 21 m/min. Holding force 65 t |
| Tugger/Mooring winch: | 10 t 12m/min. |
| Towing hook: | SWL: 15 t |
| Bow roller: | Yes |



GENERAL ARRANGEMENT

