

# Jif Vanguard


Shoalbuster 3209

MAY 7 2026



## MAIN SPECIFICATIONS

### General

Type of vessel:	Multi-Purpose Tug
Classification:	BV  HULL • MACH / TUG • Unrestricted Navigation / AUT-UMS
IMO:	9688673
Callsign:	J8B5082
MMSI:	375007000
Flag:	Dutch
Tonnage (UMS):	327

### Performances

Bollard Pull ahead:	50.70 t
Bollard Pull:	50.70 t

### Tank Capacities

Fuel oil:	222.80 m <sup>3</sup>
Fresh water:	40.90 m <sup>3</sup>
Black/grey water:	3.30 m <sup>3</sup>
Dirty oil:	4.30 m <sup>3</sup>

### Dimensions

Length O.A.:	32.08 m
Beam O.A.:	9.10 m
Draught aft (range):	2.90 – 3.20 m
Clear Deck Area:	68,75 m <sup>2</sup>
Deck loading:	10 t/m <sup>2</sup>

JIFMAR GROUP

→ Contact: sales@jifmar.net



This document is for guidance and information only. Information provided is given under good faith and is non-contractual. This document may be updated without advanced notice. It may not be published, redistributed or reproduced without the prior written consent of ©Jifmar Group.



## DETAILED SPECIFICATIONS

### Propulsion System

Bow thruster:	185 kW
Stern thruster:	No
Main engines:	2 x CATERPILLAR 3512B TA/ C HD
Power output:	2610 kW

### Auxiliary Systems

Generator sets:	2 x CATERPILLAR C4.4 + 1 x CATERPILLAR C18
-----------------	--

### Accommodation

POB:	7
Cabins:	3 x single 2 x double

### Deck Lay-out

Crane AFT:	Heila HLRM 170-4SL
Anchor handling winch:	100t/150t (pull/hold)
Towing winch:	50t/150t (pull/hold)
Tugger winches:	12 t (pull /hold)
Stern roller:	SWL 100 t
Towing pins:	50 t



## GENERAL ARRANGEMENTS

