

Jif Juliett

Shoalbuster 3209

SEPT 14 2026



MAIN SPECIFICATIONS

General

Type of vessel:	Multi-Purpose Tug
Classification:	BV HULL • MACH / Fire fighting 1 – water spraying – Anchor Handling vessel tug / Unrestricted Navigation / AUT-UMS
IMO:	9778387
Callsign:	PCRG
MMSI:	244181000
Flag:	Dutch
Tonnage (UMS):	335

Performances

Bollard Pull ahead:	47 t
Bollard Pull:	47 t

Tank Capacities

Fuel oil:	215 m ³
Fresh water:	40 m ³
Black/grey water:	3.30 m ³
Dirty oil:	4.30 m ³

Dimensions

Length O.A.:	32.27 m
Beam O.A.:	9.35 m
Draught aft (range):	2.90 – 3.20 m
Clear Deck Area:	80 m ²
Deck loading:	5 t/m ²

JIFMAR GROUP

→ Contact: sales@jifmar.net



This document is for guidance and information only. Information provided is given under good faith and is non-contractual. This document may be updated without advanced notice. It may not be published, redistributed or reproduced without the prior written consent of ©Jifmar Group.



DETAILED SPECIFICATIONS

Propulsion System

Bow thruster:	260 kW
Stern thruster:	No
Main engines:	2 x CATERPILLAR 3512C TTA/ HD
Power output:	2610 kW

Auxiliary Systems

Generator sets:	2 x CATERPILLAR C4.4 + 1 x CATERPILLAR C18
-----------------	--

Accommodation

POB:	10
Cabins:	2 x single 4 x double

Deck Lay-out

Crane AFT:	Heila HLRM 170-4SL
Anchor handling winch:	100t/150t (pull/hold)
Towing winch:	50t/150t (pull/hold)
Tugger winches:	12t (pull /hold)
Stern roller:	SWL 100 t
Towing pins:	50 t

This document is for guidance and information only. Information provided is given under good faith and is non-contractual. This document may be updated without advanced notice. It may not be published, redistributed or reproduced without the prior written consent of ©Jifmar Group.